


TEST SCHEDULE B 14	EN 1993-1-1: 2005 (EUROCODE 3)	Sargon ©, Cescoplus ©
BUCKLING	BENDING 2 (LATERAL TORSIONAL)	EC3.BUC.M2.003



Program: WEURO © version October 2007 for Sargon and Cescoplus
Keywords: EN 1993, Eurocode 3, example, validation, benchmark, reliability, quality control, error measure. **Parole chiave:** Eurocodice 3, esempio, validazione, test, affidabilità, controllo di qualità, misura dell'errore
Tv=exploitation target value, **Cv**=exploitation computed value
Authors: Ing. Marco Croci, Ing. Paolo Rugarli

BEAM						
Length [mm]		Buckling factors		Left end	Right end	
3500		$\beta_1=2$	$\beta_2=2$	$\beta_3=2$	FREE	FIXED
LOAD						
Type			Value		Point of application	
BENDING MOMENT M_2			M=800.000.000Nmm		LEFT END	
MATERIAL		S235				
f_y [N/mm ²]	f_u [N/mm ²]	E [N/mm ²]	ν	γ_{M0}	γ_{M1}	γ_{M2}
235	360	2,10E+05	0,3	1,1	1,1	1,25
CROSS-SECTION		HE 300 M		CLASS: $M_2 \rightarrow 1$		
A [mm ²]	J_2 [mm ⁴]	J_3 [mm ⁴]	J_t [mm ⁴]	W_2 [mm ³]	W_3 [mm ³]	
30308	5,920E+08	1,940E+08	1,408E+07	3,482E+06	1,252e+06	
W_{pl2} [mm ³]	W_{pl3} [mm ³]	i_2 [mm]	i_3 [mm]	i_t [mm]		
4,078E+06	1,913E+06	139,8	80	89,49		
h	b	t_w	t_f	r		
340	310	21	39	27		
OTHER DATA*						
h/b		α_{LT}	I_ω	G		
1,10		0,21	4,386E+12	8,077E+04		
χ_{LT}	ϕ_{LT}	λ_{LT}	M_{cr}	C_1		
0.926	0.653	0.494	3.927E+09	1		

TARGET VALUES BASED ON PRELIMINAR COMPUTATIONS

$$T_v = M / (\chi_{LT} W_{pl} f_y / \gamma_{M1})$$

T_v
9,915E-01

CHECKER'S RESULTS (COMPUTED VALUES) AND COMPARISON WITH THE TARGET

C_v	$(C_v - T_v) / T_v$
9,916E-01	8,860E-05

In Sargon was fixed the same C_1 value reported in Other Data section