


TEST SCHEDULE B 16	EN 1993-1-1: 2005 (EUROCODE 3)	Sargon ©, Cescoplus ©
BUCKLING	BENDING 2 (LATERAL TORSIONAL)	EC3.BUC.Q3.001



Program: WEURO © version October 2007 for Sargon and Cescoplus
Keywords: EN 1993, Eurocode 3, example, validation, benchmark, reliability, quality control, error measure. **Parole chiave:** Eurocodice 3, esempio, validazione, test, affidabilità, controllo di qualità, misura dell'errore
Tv=exploitation target value, **Cv**=exploitation computed value
Authors: Ing. Marco Croci, Ing. Paolo Rugarli

BEAM						
Length [mm]	Buckling factors		Left end		Right end	
3500	$\beta_1=1$	$\beta_2=1$	$\beta_3=1$	FREE		FIXED
LOAD						
Type		Value		Point of application		
DISTRIBUTED LOAD q_3		$q=80\text{N/mm}$				
MATERIAL		S235				
f_y [N/mm ²]	f_u [N/mm ²]	E [N/mm ²]	ν	γ_{M0}	γ_{M1}	γ_{M2}
235	360	2,10E+05	0,3	1,1	1,1	1,25
CROSS-SECTION		HE 240 A		CLASS: $M_2 \rightarrow 1$		
A [mm ²]	J_2 [mm ⁴]	J_3 [mm ⁴]	J_t [mm ⁴]	W_2 [mm ³]	W_3 [mm ³]	
7684	7,763E+07	2,769E+07	4,155E+05	6,751E+05	2,307E+05	
W_{pl2} [mm ³]	W_{pl3} [mm ³]	i_2 [mm]	i_3 [mm]	i_t [mm]		
7,446E+05	3,517E+05	100,5	60	69,28		
h	b	t_w	t_f	r		
230	240	7,5	12	21		
OTHER DATA*						
h/b	α_{LT}	I_ω	G			
0,96	0,21	3,285E+11	8,077E+04			
χ_{LT}	ϕ_{LT}	λ_{LT}	M_{cr}	C_1		
0.928	0.650	0.489	7,315E+08	1.132		

TARGET VALUES BASED ON PRELIMINAR COMPUTATIONS

$$T_v = M / (\chi_{LT} W_{pl} f_y / \gamma_{M1})$$

T_v
8,302E-01

CHECKER'S RESULTS (COMPUTED VALUES) AND COMPARISON WITH THE TARGET

C_v	$(C_v - T_v) / T_v$
8,301E-01	-7,756E-05

In Sargon was fixed the same C_1 value reported in Other Data section