


TEST SCHEDULE R 12	EN 1993-1-1: 2005 (EUROCODE 3)	Sargon ©, Cescoplus ©
RESISTANCE	BENDING - AXIS 2	EC3.RES.M2.001



Program: WEURO © version October 2007 for Sargon and Cescoplus
Keywords: EN 1993, Eurocode 3, example, validation, benchmark, reliability, quality control, error measure. **Parole chiave:** Eurocodice 3, esempio, validazione, test ,affidabilità, controllo di qualità, misura dell'errore
Tv=exploitation target value, **Cv**=exploitation computed value
Authors: Ing. Marco Croci, Ing. Paolo Rugarli

BEAM		
Length [mm]	Left end	Right end
1000	FREE	FIXED

LOAD		
Type	Value	Point of application
BENDING MOMENT M_2	$M=3.000.000\text{Nmm}$	LEFT END

MATERIAL	A588/42					
f_y [N/mm ²]	f_u [N/mm ²]	E [N/mm ²]	ν	γ_{M0}	γ_{M1}	γ_{M2}
290	434	2,000e+05	0,3	1,1	1,1	1,25

CROSS SECTION	O 54x3,2	CLASS: $M_2 \rightarrow 1$				
A [mm ²]	J_2 [mm ⁴]	J_3 [mm ⁴]	J_t [mm ⁴]	W_2 [mm ³]	W_3 [mm ³]	
510,7	1,654e+05	1,654e+05	3,308e+05	6,126e+03	6,126e+03	
W_{pl2} [mm ³]	W_{pl3} [mm ³]	i_2 [mm]	i_3 [mm]	i_t [mm]		
8,269E+03	8,269E+03	18	18	0		

OTHER DATA					

TARGET VALUES BASED ON PRELIMINAR COMPUTATIONS

$$M_{pl,Rd} = W_{pl} \cdot f_y / \gamma_{M0}$$

$T_v = M / M_{pl,Rd}$
1,376E+00

CHECKER'S RESULTS (COMPUTED VALUES) AND COMPARISON WITH THE TARGET

C_v	$(C_v - T_v) / T_v$
1,376E+00	-1,060E-04