


TEST SCHEDULE R 25	EN 1993-1-1: 2005 (EUROCODE 3)	Sargon ©, Cescoplus ©
RESISTANCE	SHEAR – AXIS 3	EC3.RES.T3.005



Program: WEURO © version October 2007 for Sargon and Cescoplus
Keywords: EN 1993, Eurocode 3, example, validation, benchmark, reliability, quality control, error measure. **Parole chiave:** Eurocodice 3, esempio, validazione, test ,affidabilità, controllo di qualità, misura dell'errore
Tv=exploitation target value, **Cv**=exploitation computed value
Authors: Ing. Marco Croci, Ing. Paolo Rugarli

BEAM						
Length [mm]		Left end			Right end	
1000		HINGE			HINGE	
LOAD						
Type		Value		Point of application		
SHEAR FORCE T ₃		T=1.000.000N		MIDDLE POINT		
MATERIAL	S490					
f _y [N/mm ²]	f _u [N/mm ²]	E [N/mm ²]	ν	γ _{M0}	γ _{M1}	γ _{M2}
490	570	2,10E+05	0,3	1,1	1,1	1,25
CROSS-SECTION		HE 200 B				
A [mm ²]	J ₂ [mm ⁴]	J ₃ [mm ⁴]	J _t [mm ⁴]	W ₂ [mm ³]	W ₃ [mm ³]	
7808	5,696e+07	2,003e+07	5,928e+05	5,696e+05	2,003e+05	
W _{pl2} [mm ³]	W _{pl3} [mm ³]	i ₂ [mm]	i ₃ [mm]	i _t [mm]		
6,426e+05	3,058e+05	85,40	50,70	57,74		
h	b	t _w	t _f	r		
200	200	9	15	18		
OTHER DATA						
A _V =A-2bt _f +(t _w +2r)t _f [mm ²]						
2.483						

TARGET VALUES BASED ON PRELIMINAR COMPUTATIONS

$$V_{pl,Rd}=A_v \cdot (f_y / \sqrt{3}) / \gamma_{M0}$$

$T_v=T / V_{pl,Rd}$
7,830E-01

CHECKER'S RESULTS (COMPUTED VALUES) AND COMPARISON WITH THE TARGET

C_v	$(C_v-T_v)/T_v$
7,830E-01	2,589E-05

Only member's extreme sections were considered in the check in order to get bending moment $M_2=0$, always

Copyright © 2007 Castalia srl – Milan – Italy – All rights reserved: data may be used but citing the source and informing Castalia srl.

<http://www.castaliaweb.com>
staff@castaliaweb.com